



Made To Order
 Cut To Length
 Stocking Program Available

M16878/11 | MIL-W-16878/11 Type K Wire | Nema HP4 Type K

| MIL-W-16878/11 Type K Wire (M16878/11) Nema HP4 Type K | | | | | |
|--|-----|----------|-------------------------|-------------------|-------------|
| Mil-Spec # | AWG | Standing | Nom. Dia. of Cond. (in) | Nominal O.D. (in) | Nom. Weight |
| M16878/11BDB | 26 | 7/34 | 0.019 | 0.039 | 2 Lbs/Mft |
| M16878/11BDE | 26 | 19/38 | 0.019 | 0.039 | 2 Lbs/Mft |
| M16878/11BEA | 24 | Solid | 0.02 | 0.04 | 3 Lbs/Mft |
| M16878/11BEB | 24 | 7/32 | 0.024 | 0.044 | 3 Lbs/Mft |
| M16878/11BEE | 24 | 19/36 | 0.024 | 0.044 | 3 Lbs/Mft |
| M16878/11BFA | 22 | Solid | 0.025 | 0.045 | 4 Lbs/Mft |
| M16878/11BFB | 22 | 7/30 | 0.03 | 0.05 | 4 Lbs/Mft |
| M16878/11BFE | 22 | 19/34 | 0.03 | 0.05 | 4 Lbs/Mft |
| M16878/11BGA | 20 | Solid | 0.032 | 0.05 | 5 Lbs/Mft |
| M16878/11BGB | 20 | 7/28 | 0.036 | 0.058 | 5 Lbs/Mft |
| M16878/11BGE | 20 | 19/32 | 0.038 | 0.058 | 5 Lbs/Mft |
| M16878/11BHB | 18 | 7/26 | 0.048 | 0.069 | 8 Lbs/Mft |
| M16878/11BHE | 18 | 19/30 | 0.047 | 0.069 | 8 Lbs/Mft |
| M16878/11BJE | 16 | 19/29 | 0.053 | 0.08 | 10 Lbs/Mft |
| M16878/11BKE | 14 | 19/27 | 0.067 | 0.094 | 15 Lbs/Mft |
| M16878/11BLE | 12 | 19/25 | 0.084 | 0.113 | 23 Lbs/Mft |
| M16878/11BMG | 10 | 37/26 | 0.11 | 0.132 | 35 Lbs/Mft |
| M16878/11BNL | 8 | 133/29 | 0.162 | 0.19 | 60 Lbs/Mft |

*Tables are illustrative and not exhaustive. Please consult the factory for more information.