



Made To Order
 Cut To Length
 Stocking Program Available

M16878/4 | MIL-W-16878/4 Type E Wire | Nema HP3 Type E

| M16878/4 MIL-W-16878/4 Type E Wire Nema HP3 Type E | | | | | |
|--|-----|----------|------------------------|-------------------|-------------|
| Mil-Spec # | AWG | Standing | Nom. Insul. Thick (in) | Nominal O.D. (in) | Nom. Weight |
| M16878/4BDA | 26 | Solid | 0.01 | 0.036 | 2 Lbs/Mft |
| M16878/4BDE | 26 | 19/38 | 0.01 | 0.039 | 2 Lbs/Mft |
| M16878/4BDB | 26 | 7/34 | 0.01 | 0.04 | 2 Lbs/Mft |
| M16878/4BEA | 24 | Solid | 0.01 | 0.04 | 3 Lbs/Mft |
| M16878/4BEB | 24 | 7/32 | 0.01 | 0.044 | 3 Lbs/Mft |
| M16878/4BEE | 24 | 19/36 | 0.01 | 0.045 | 3 Lbs/Mft |
| M16878/4BFA | 22 | Solid | 0.01 | 0.045 | 4 Lbs/Mft |
| M16878/4BFB | 22 | 7/30 | 0.01 | 0.05 | 4 Lbs/Mft |
| M16878/4BFE | 22 | 19/34 | 0.01 | 0.051 | 4 Lbs/Mft |
| M16878/4BGA | 20 | Solid | 0.01 | 0.052 | 5 Lbs/Mft |
| M16878/4BGB | 20 | 7/28 | 0.01 | 0.058 | 5 Lbs/Mft |
| M16878/4BGE | 20 | 19/32 | 0.01 | 0.058 | 6 Lbs/Mft |
| M16878/4BHA | 18 | Solid | 0.01 | 0.06 | 8 Lbs/Mft |
| M16878/4BHB | 18 | 7/26 | 0.01 | 0.069 | 8 Lbs/Mft |
| M16878/4BHE | 18 | 19/30 | 0.01 | 0.069 | 8 Lbs/Mft |
| M16878/4BJE | 16 | 19/29 | 0.013 | 0.08 | 10 Lbs/Mft |
| M16878/4BKE | 14 | 19/27 | 0.013 | 0.095 | 15 Lbs/Mft |
| M16878/4BLE | 12 | 19/25 | 0.015 | 0.114 | 23 Lbs/Mft |
| M16878/4BMG | 10 | 37/26 | 0.015 | 0.134 | 35 Lbs/Mft |

*Tables are illustrative and not exhaustive. Please consult the factory for more information.