



Made To Order
 Cut To Length
 Stocking Program Available

M16878/17 | MIL-W-16878/17 Type BN Wire

MIL-W-16878/17 Type BN (M16878/17)					
Mil-Spec #	AWG	Stranding	Nom. Conductor O.D. (in)	Nom. O.D. (in)	Nom. Weight
M16878/17BDA	26	Solid	0.016	0.042	2 Lbs/Mft
M16878/17BDB	26	7/34	0.018	0.045	3 Lbs/Mft
M16878/17BDE	26	19/38	0.018	0.045	2 Lbs/Mft
M16878/17BEA	24	Solid	0.02	0.046	3 Lbs/Mft
M16878/17BEB	24	7/32	0.024	0.05	3 Lbs/Mft
M16878/17BEE	24	19/36	0.024	0.05	3 Lbs/Mft
M16878/17BFA	22	Solid	0.025	0.052	5 Lbs/Mft
M16878/17BFB	22	7/30	0.031	0.056	5 Lbs/Mft
M16878/17BFE	22	19/34	0.031	0.056	5 Lbs/Mft
M16878/17BGA	20	Solid	0.032	0.058	7 Lbs/Mft
M16878/17BGB	20	7/28	0.038	0.064	7 Lbs/Mft
M16878/17BGE	20	19/32	0.038	0.064	7 Lbs/Mft
M16878/17BHB	18	7/26	0.048	0.074	10 Lbs/Mft
M16878/17BHE	18	19/30	0.048	0.074	10 Lbs/Mft
M16878/17BJA	16	Solid	0.05	0.079	13 Lbs/Mft
M16878/17BJE	16	19/29	0.059	0.085	13 Lbs/Mft
M16878/17BKE	14	19/27	0.073	0.099	15 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.