



Made To Order  
 Cut To Length  
 Stocking Program Available

**M16878/19 | MIL-W-16878/19 Type DN Wire**

MIL-W-16878/19 Type DN (M16878/19)					
Mil-Spec #	AWG	Stranding	Nom.Conductor O.D. (in)	Nom. O.D. (in)	Nom. Weight
M16878/19BEA	24	Solid	0.02	0.089	5 Lbs/Mft
M16878/19BEB	24	7/32	0.024	0.092	5 Lbs/Mft
M16878/19BEE	24	19/36	0.024	0.092	5 Lbs/Mft
M16878/19BFA	22	Solid	0.025	0.095	5 Lbs/Mft
M16878/19BFB	22	7/30	0.031	0.1	5 Lbs/Mft
M16878/19BFE	22	19/34	0.031	0.1	6 Lbs/Mft
M16878/19BGA	20	Solid	0.032	0.101	7 Lbs/Mft
M16878/19BGB	20	7/28	0.038	0.106	8 Lbs/Mft
M16878/19BGE	20	19/32	0.038	0.106	8 Lbs/Mft
M16878/19BHB	18	7/26	0.048	0.117	10 Lbs/Mft
M16878/19BHE	18	19/30	0.048	0.117	11 Lbs/Mft
M16878/19BJA	16	Solid	0.05	0.122	13 Lbs/Mft
M16878/19BJE	16	19/29	0.054	0.126	13 Lbs/Mft
M16878/19BKE	14	19/27	0.073	0.138	18 Lbs/Mft
M16878/19BLE	12	19/25	0.089	0.168	28 Lbs/Mft
M16878/19BMG	10	37/26	0.107	0.192	41 Lbs/Mft

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.