



Made To Order
Cut To Length
Stocking Program Available

M16878/5 | MIL-W-16878/5 Type EE Wire | Nema HP3 Type EE

MIL-W-16878/5 Type EE Wire (M16878/5) Nema HP3 Type EE					
Mil-Spec #	AWG	Standing	Nom. Insul. Thick (in)	Nominal O.D. (in)	Nom. Weight
M16878/5BEB	24	7/32	0.015	0.052	3.05 Lbs/Mft
M16878/5BEE	24	19/36	0.015	0.052	3.13 Lbs/Mft
M16878/5BFB	22	7/30	0.015	0.058	4.11 Lbs/Mft
M16878/5BFE	22	19/34	0.015	0.058	4.25 Lbs/Mft
M16878/5BGB	20	7/28	0.015	0.066	5.75 Lbs/Mft
M16878/5BGE	20	19/32	0.015	0.066	5.99 Lbs/Mft
M16878/5BHB	18	7/26	0.015	0.076	8.42 Lbs/Mft
M16878/5BHE	18	19/30	0.015	0.076	8.64 Lbs/Mft
M16878/5BJE	16	19/.0117	0.015	0.085	10.99 Lbs/Mft
M16878/5BKE	14	19/.0147	0.015	0.1	16.45 Lbs/Mft
M16878/5BLE	12	19/.0185	0.015	0.12	24.61 Lbs/Mft
M16878/5BMG	10	37/.0157	0.015	0.143	36.61 Lbs/Mft
M16878/5BNL	8	133/29	0.024	0.209	68 Lbs/Mft
M16878/5BPL	6	133/27	0.028	0.263	107 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.