



Made To Order  
 Cut To Length  
 Stocking Program Available

**M16878/18 | MIL-W-16878/18 Type CN Wire**

MIL-W-16878/18 Type CN (M16878/18)					
Mil-Spec #	AWG	Stranding	Nom. Conductor O.D. (in)	Nom. O.D. (in)	Nom. Weight
M16878/18BDA	26	Solid	0.016	0.056	3 Lbs/Mft
M16878/18BDB	26	7/34	0.018	0.059	3 Lbs/Mft
M16878/18BDE	26	19/38	0.018	0.059	3 Lbs/Mft
M16878/18BEA	24	Solid	0.02	0.06	3 Lbs/Mft
M16878/18BEB	24	7/32	0.024	0.064	3 Lbs/Mft
M16878/18BEE	24	19/36	0.024	0.064	3 Lbs/Mft
M16878/18BFA	22	Solid	0.025	0.065	4 Lbs/Mft
M16878/18BFB	22	7/30	0.031	0.07	4 Lbs/Mft
M16878/18BFE	22	19/34	0.031	0.07	4 Lbs/Mft
M16878/18BGA	20	Solid	0.032	0.072	6 Lbs/Mft
M16878/18BGB	20	7/28	0.038	0.078	6 Lbs/Mft
M16878/18BGE	20	19/32	0.038	0.078	6 Lbs/Mft
M16878/18BHB	18	7/26	0.048	0.09	8 Lbs/Mft
M16878/18BHE	18	19/30	0.048	0.09	8 Lbs/Mft
M16878/18BJA	16	Solid	0.051	0.093	11 Lbs/Mft
M16878/18BJE	16	19/29	0.059	0.099	11 Lbs/Mft
M16878/18BKE	14	19/27	0.073	0.113	16 Lbs/Mft
M16878/18BLE	12	19/25	0.089	0.132	26 Lbs/Mft

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.