



Made To Order  
Cut To Length  
Stocking Program Available

#### Multi-conductor VNTC: Unshielded

| 18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.020" (0,51mm) |                 |          |            |             |         |             |
|--|-----------------|----------|------------|-------------|---------|-------------|
| Part Number  | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| 2318   | 3               | 0.015    | 0.005      | 0.045       | 0.285   | 44 Lbs/Mft  |
| 2518   | 5               | 0.015    | 0.005      | 0.045       | 0.335   | 65 Lbs/Mft  |
| 2918   | 9               | 0.015    | 0.005      | 0.045       | 0.42    | 103 Lbs/Mft |
| 2018-12C   | 12              | 0.015    | 0.005      | 0.045       | 0.46    | 129 Lbs/Mft |
| 2018-15C   | 15              | 0.015    | 0.005      | 0.045       | 0.505   | 156 Lbs/Mft |
| 2018-19C   | 19              | 0.015    | 0.005      | 0.045       | 0.575   | 206 Lbs/Mft |
| 2018-25C   | 25              | 0.015    | 0.005      | 0.045       | 0.65    | 265 Lbs/Mft |
| 2018-37C   | 37              | 0.015    | 0.005      | 0.045       | 0.755   | 370 Lbs/Mft |

| 16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.020" (0,51mm) |                 |          |            |             |         |             |
|--|-----------------|----------|------------|-------------|---------|-------------|
| Part Number  | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| 2316   | 3               | 0.015    | 0.005      | 0.045       | 0.305   | 59 Lbs/Mft  |
| 2516   | 5               | 0.015    | 0.005      | 0.045       | 0.36    | 85 Lbs/Mft  |
| 2916   | 9               | 0.015    | 0.005      | 0.045       | 0.46    | 137 Lbs/Mft |
| 2016-12C   | 12              | 0.015    | 0.005      | 0.045       | 0.5     | 177 Lbs/Mft |
| 2016-15C   | 15              | 0.015    | 0.005      | 0.06        | 0.58    | 230 Lbs/Mft |
| 2016-19C   | 19              | 0.015    | 0.005      | 0.06        | 0.625   | 278 Lbs/Mft |
| 2016-25C   | 25              | 0.015    | 0.005      | 0.06        | 0.71    | 360 Lbs/Mft |
| 2016-37C   | 37              | 0.015    | 0.005      | 0.06        | 0.865   | 510 Lbs/Mft |

| 14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm) |                 |          |            |             |         |             |
|--|-----------------|----------|------------|-------------|---------|-------------|
| Part Number  | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| 2314   | 3               | 0.015    | 0.005      | 0.045       | 0.34    | 81 Lbs/Mft  |
| 2514   | 5               | 0.015    | 0.005      | 0.045       | 0.4     | 117 Lbs/Mft |
| 2014-9C  | 9               | 0.015    | 0.005      | 0.045       | 0.505   | 191 Lbs/Mft |
| 2014-15C   | 15              | 0.015    | 0.005      | 0.06        | 0.645   | 321 Lbs/Mft |
| 2014-19C   | 19              | 0.015    | 0.005      | 0.06        | 0.695   | 393 Lbs/Mft |
| 2014-25C   | 25              | 0.015    | 0.005      | 0.06        | 0.79    | 507 Lbs/Mft |
| 2014-30C   | 30              | 0.015    | 0.005      | 0.08        | 0.895   | 635 Lbs/Mft |
| 2014-37C   | 37              | 0.015    | 0.005      | 0.08        | 0.965   | 762 Lbs/Mft |

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order  
Cut To Length  
Stocking Program Available

12 AWG (2,34mm), 7/.0305 (7x0,77mm), Insulation Thickness: 0.020" (0,51mm)

| Part Number | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight       |
|-------------|-----------------|----------|------------|-------------|---------|--------------|
| 2312        | 3               | 0.015    | 0.005      | 0.045       | 0.385   | 114 Lbs/Mft  |
| 2512        | 5               | 0.015    | 0.005      | 0.045       | 0.455   | 165 Lbs/Mft  |
| 2912        | 9               | 0.015    | 0.005      | 0.06        | 0.61    | 293 Lbs/Mft  |
| 2012-15C    | 15              | 0.015    | 0.005      | 0.06        | 0.735   | 460 Lbs/Mft  |
| 2012-19C    | 19              | 0.015    | 0.005      | 0.06        | 0.795   | 564 Lbs/Mft  |
| 2012-25C    | 25              | 0.015    | 0.005      | 0.08        | 0.945   | 769 Lbs/Mft  |
| 2012-30C    | 30              | 0.015    | 0.005      | 0.08        | 1.025   | 908 Lbs/Mft  |
| 2012-37C    | 37              | 0.015    | 0.005      | 0.08        | 1.105   | 1099 Lbs/Mft |

10 AWG (2,92mm), 7/.0385 (7x0,98mm), Insulation Thickness: 0.020" (0,51mm)

| Part Number | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
|-------------|-----------------|----------|------------|-------------|---------|-------------|
| 2310        | 3               | 0.02     | 0.005      | 0.045       | 0.45    | 165 Lbs/Mft |
| 2410        | 4               | 0.02     | 0.005      | 0.045       | 0.495   | 209 Lbs/Mft |
| 2510        | 5               | 0.02     | 0.005      | 0.06        | 0.575   | 264 Lbs/Mft |
| 2710        | 7               | 0.02     | 0.005      | 0.06        | 0.625   | 343 Lbs/Mft |
| 2910        | 9               | 0.02     | 0.005      | 0.06        | 0.73    | 443 Lbs/Mft |
| 2010-12C    | 12              | 0.02     | 0.005      | 0.06        | 0.8     | 575 Lbs/Mft |

8 AWG (3,70mm), 7/.0486 (7x1,23mm), Insulation Thickness: 0.035" (0,89mm)

| Part Number | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
|-------------|-----------------|----------|------------|-------------|---------|-------------|
| 2308        | 3               | 0.03     | 0.005      | 0.06        | 0.585   | 255 Lbs/Mft |
| 2408        | 4               | 0.03     | 0.005      | 0.06        | 0.641   | 327 Lbs/Mft |
| 2508        | 5               | 0.03     | 0.005      | 0.06        | 0.703   | 399 Lbs/Mft |
| 2708        | 7               | 0.03     | 0.005      | 0.06        | 0.768   | 471 Lbs/Mft |
| 2908        | 9               | 0.03     | 0.005      | 0.08        | 0.94    | 715 Lbs/Mft |
| 2008-12C    | 12              | 0.03     | 0.005      | 0.08        | 1.057   | 926 Lbs/Mft |

6 AWG (4,67mm), 7/.0612 (7x1,55mm), Insulation Thickness: 0.035" (0,89mm)

| Part Number | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight       |
|-------------|-----------------|----------|------------|-------------|---------|--------------|
| 2306        | 3               | 0.03     | 0.005      | 0.06        | 0.667   | 364 Lbs/Mft  |
| 2406        | 4               | 0.03     | 0.005      | 0.06        | 0.733   | 470 Lbs/Mft  |
| 2506        | 5               | 0.03     | 0.005      | 0.06        | 0.806   | 576 Lbs/Mft  |
| 2706        | 7               | 0.03     | 0.005      | 0.08        | 0.922   | 813 Lbs/Mft  |
| 2906        | 9               | 0.03     | 0.005      | 0.08        | 1.078   | 1032 Lbs/Mft |
| 2006-12C    | 12              | 0.03     | 0.005      | 0.08        | 1.215   | 1345 Lbs/Mft |

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.