



Made To Order  
Cut To Length  
Stocking Program Available

**Multi-pair Electronic Cable: MultiShield (Foil & Braid) - PVC Insulated & Jacketed**

24 AWG (0,23mm<sup>2</sup>), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8024-2PSFSB	2	0.03	0,81	0.23	5,8
L8024-3PSFSB	3	0.03	0,81	0.25	6,5
L8024-6PSFSB	6	0.03	0,81	0.31	8,0
L8024-9PSFSB	9	0.03	0,81	0.36	9,1
L8024-11PSFSB	11	0.03	0,81	0.38	9,7
L8024-15PSFSB	15	0.03	0,81	0.43	10,8
L8024-19PSFSB	19	0.03	0,81	0.46	11,8
L8024-27PSFSB	27	0.03	0,81	0.53	13,4

22 AWG (0,35mm<sup>2</sup>), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8022-2PSFSB	2	0.03	0,81	0.25	6,3
L8022-4PSFSB	4	0.03	0,81	0.31	7,8
L8022-6PSFSB	6	0.03	0,81	0.35	8,9
L8022-9PSFSB	9	0.03	0,81	0.4	10,1
L8022-11PSFSB	11	0.03	0,81	0.43	10,9
L8022-15PSFSB	15	0.03	0,81	0.48	12,1
L8022-19PSFSB	19	0.03	0,81	0.52	13,2
L8022-27PSFSB	27	0.05	1,35	0.64	16,2

20 AWG (0,56mm<sup>2</sup>), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-2PSFSB	2	0.03	0,81	0.33	8,3
L8020-3PSFSB	3	0.03	0,81	0.35	8,9
L8020-6PSFSB	6	0.03	0,81	0.45	11,3
L8020-9PSFSB	9	0.03	0,81	0.52	13,0
L8020-12PSFSB	12	0.03	0,81	0.56	14,1
L8020-19PSFSB	19	0.05	1,35	0.72	18,4

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order  
 Cut To Length  
 Stocking Program Available

18 AWG (0,81mm <sup>2</sup> ), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8018-3PSFSB	3	0.03	0,81	0.39	9,8
L8018-6PSFSB	6	0.03	0,81	0.49	12,5
L8018-9PSFSB	9	0.05	1,35	0.62	15,6
L8018-27PSFSB	27	0.08	2,11	0.98	24,9

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.