



Made To Order  
Cut To Length  
Stocking Program Available

**Multi-pair Electronic Cable: Overall Foil Shield - PVC Insulated & Jacketed**

24 AWG (0,23mm<sup>2</sup>), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8024-2PS	2	0.03	0,81	0.21	5,2
L8024-3PS	3	0.03	0,81	0.23	5,9
L8024-6PS	6	0.03	0,81	0.29	7,4
L8024-9PS	9	0.03	0,81	0.34	8,5
L8024-11PS	11	0.03	0,81	0.36	9,2
L8024-15PS	15	0.03	0,81	0.4	10,3
L8024-19PS	19	0.03	0,81	0.44	11,2
L8024-27PS	27	0.03	0,81	0.5	12,8

22 AWG (0,35mm<sup>2</sup>), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8022-2PS	2	0.03	0,81	0.23	5,8
L8022-4PS	4	0.03	0,81	0.27	7,0
L8022-6PS	6	0.03	0,81	0.32	8,0
L8022-9PS	9	0.03	0,81	0.37	9,4
L8022-11PS	11	0.03	0,81	0.4	10,3
L8022-15PS	15	0.03	0,81	0.45	11,4
L8022-19PS	19	0.03	0,81	0.49	12,5
L8022-27PS	27	0.05	1,35	0.62	15,7

20 AWG (0,56mm<sup>2</sup>), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-2PS	2	0.03	0,81	0.3	7,7
L8020-3PS	3	0.03	0,81	0.33	8,3
L8020-6PS	6	0.03	0,81	0.42	10,7
L8020-9PS	9	0.03	0,81	0.49	12,5
L8020-12PS	12	0.03	0,81	0.53	13,5
L8020-19PS	19	0.05	1,35	0.7	17,8

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order  
Cut To Length  
Stocking Program Available

18 AWG (0,81mm <sup>2</sup> ), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8018-3PS	3	0.03	0,81	0.36	9,2
L8018-6PS	6	0.03	0,81	0.47	12,0

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.