



Made To Order
Cut To Length
Stocking Program Available

Multi-pair Electronic Cable: Unshielded - PVC Insulated & Jacketed

24 AWG (0,23mm²), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8224	1	0.03	0,81	0.16	4,1
L8024-2P	2	0.03	0,81	0.2	5,1
L8024-3P	3	0.03	0,81	0.23	5,8
L8024-4P	4	0.03	0,81	0.25	6,4
L8024-5P	5	0.03	0,81	0.27	6,9
L8024-6P	6	0.03	0,81	0.29	7,3
L8024-9P	9	0.03	0,81	0.33	8,4
L8024-11P	11	0.03	0,81	0.36	9,1
L8024-15P	15	0.03	0,81	0.4	10,1
L8024-27P	27	0.03	0,81	0.5	12,7
L8024-77P	77	0.08	2,11	0.85	21,8

22 AWG (0,35mm²), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8222	1	0.03	0,81	0.17	4,3
L8022-2P	2	0.03	0,81	0.22	5,7
L8022-3P	3	0.03	0,81	0.25	6,5
L8022-4P	4	0.03	0,81	0.28	7,1
L8022-5P	5	0.03	0,81	0.3	7,7
L8022-6P	6	0.03	0,81	0.31	7,8
L8022-15P	15	0.03	0,81	0.45	11,5

20 AWG (0,56mm²), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-2P	2	0.03	0,81	0.3	7,5
L8020-3P	3	0.03	0,81	0.32	8,2
L8020-6P	6	0.03	0,81	0.42	10,6
L8020-9P	9	0.03	0,81	0.49	12,4
L8020-12P	12	0.03	0,81	0.53	13,5

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

18 AWG (0,81mm ²), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Pairs	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8018-2P	2	0.03	0,81	0.33	8,4
L8018-3P	3	0.03	0,81	0.36	9,1
L8018-6P	6	0.03	0,81	0.47	11,9
L8018-9P	9	0.05	1,35	0.55	13,9
L8018-12P	12	0.05	1,35	0.63	16,1

*Tables are illustrative and not exhaustive. Please consult the factory for more information.