



Made To Order
Cut To Length
Stocking Program Available

Multi-pair PLTC: Individual & Overall Shielded

20 AWG (0,91mm), 7/.0121 (7x0,32mm), Insulation Thickness: 0.015" (0,38mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2SPSN20	2	0.04	1,02	0.316	8,03	46.4
PLTC4SPSN20	4	0.04	1,02	0.325	8,26	75.9
PLTC8SPSN20	8	0.05	1,27	0.426	10,82	147.5
PLTC12SPSN20	12	0.06	1,52	0.64	16,26	223
PLTC16SPSN20	16	0.06	1,52	0.705	17,91	280
PLTC20SPSN20	20	0.06	1,52	0.78	19,81	339
PLTC24SPSN20	24	0.06	1,52	0.845	21,46	397
PLTC36SPSN20	36	0.07	1,78	1.015	25,78	586
PLTC50SPSN20	50	0.07	1,78	1.19	30,23	786

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.015" (0,38mm)

Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2SPSN18	2	0.04	1,07	0.296	7,52	61
PLTC4SPSN18	4	0.04	1,07	0.41	10,41	100
PLTC8SPSN18	8	0.06	1,52	0.485	12,32	212
PLTC12SPSN18	12	0.06	1,52	0.76	19,30	315
PLTC16SPSN18	16	0.06	1,52	0.845	21,46	401
PLTC20SPSN18	20	0.07	1,78	0.955	24,26	505
PLTC24SPSN18	24	0.07	1,78	1.04	26,42	596
PLTC36SPSN18	36	0.07	1,78	1.215	30,86	846
PLTC50SPSN18	50	0.08	2,03	1.45	36,83	1165

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2SPSN16	2	0.04	1,07	0.346	8,79	79.8
PLTC4SPSN16	4	0.05	1,35	0.506	12,85	150.9
PLTC8SPSN16	8	0.06	1,52	0.665	16,89	287.9
PLTC12SPSN16	12	0.06	1,52	0.855	21,72	435
PLTC16SPSN16	16	0.07	1,78	0.97	24,64	575
PLTC20SPSN16	20	0.07	1,78	1.08	27,43	705
PLTC24SPSN16	24	0.07	1,78	1.165	29,59	828
PLTC36SPSN16	36	0.08	2,03	1.39	35,31	1215

*Tables are illustrative and not exhaustive. Please consult the factory for more information.