



Made To Order
Cut To Length
Stocking Program Available

Multi-pair PLTC: Overall Shield

20 AWG (0,91mm), 7/.0121 (7x0,32mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2C20SF	1	0.04	1,02	0.22	5,59	28.5
PLTC2PSN20	2	0.04	1,02	0.255	6,48	41
PLTC4PSN20	4	0.045	1,09	0.327	9,31	66.5
PLTC8PSN20	8	0.05	1,27	0.475	12,07	103.5
PLTC12PSN20	12	0.05	1,27	0.545	13,84	195
PLTC16PSN20	16	0.05	1,27	0.605	15,37	248
PLTC20PSN20	20	0.06	1,52	0.65	16,51	309
PLTC24PSN20	24	0.06	1,52	0.74	18,80	376
PLTC36PSN20	36	0.06	1,52	0.85	21,59	530
PLTC50PSN20	50	0.07	1,78	0.97	24,64	715

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2C18SF	1	0.04	1,02	0.24	6,10	36
PLTC2PSN18	2	0.045	1,09	0.331	8,29	55.5
PLTC4PSN18	4	0.045	1,09	0.363	9,11	92
PLTC8PSN18	8	0.06	1,52	0.646	16,41	192.5
PLTC12PSN18	12	0.06	1,52	0.67	17,02	293
PLTC16PSN18	16	0.06	1,52	0.75	19,05	374.5
PLTC20PSN18	20	0.06	1,52	0.78	19,81	449
PLTC24PSN18	24	0.07	1,78	0.915	23,24	565
PLTC36PSN18	36	0.07	1,78	1.18	29,97	1060
PLTC50PSN18	50	0.08	2,03	1.321	33,55	1472

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Pairs	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2C16SF	1	0.04	1,02	0.275	6,94	45
PLTC2PSN16	2	0.045	1,09	0.35	8,77	75
PLTC4PSN16	4	0.055	1,37	0.485	12,24	133.5
PLTC8PSN16	8	0.06	1,52	0.726	18,44	259
PLTC12PSN16	12	0.06	1,52	0.755	19,18	408
PLTC16PSN16	16	0.07	1,78	0.845	21,46	526
PLTC20PSN16	20	0.07	1,78	0.905	22,99	655
PLTC24PSN16	24	0.07	1,78	1.03	26,16	803
PLTC36PSN16	36	0.07	1,78	1.165	29,59	1125

*Tables are illustrative and not exhaustive. Please consult the factory for more information.