



Made To Order
Cut To Length
Stocking Program Available

Multi-pair VNTC: Individual & Overall Shielded

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2018-2SPSN	2	0.015	0.005	0.045	0.47	74 Lbs/Mft
2018-4SPSN	4	0.015	0.005	0.045	0.52	120 Lbs/Mft
2018-6SPSN	6	0.015	0.005	0.06	0.61	178 Lbs/Mft
2018-8SPSN	8	0.015	0.005	0.06	0.72	221 Lbs/Mft
2018-10SPSN	10	0.015	0.005	0.06	0.79	247 Lbs/Mft
2018-12SPSN	12	0.015	0.005	0.06	0.84	309 Lbs/Mft
2018-16SPSN	16	0.015	0.005	0.08	0.96	395 Lbs/Mft
2018-20SPSN	20	0.015	0.005	0.08	1.05	474 Lbs/Mft
2018-24SPSN	24	0.015	0.005	0.08	1.2	602 Lbs/Mft
2018-36SPSN	36	0.015	0.005	0.08	1.4	848 Lbs/Mft

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2016-2SPSN	2	0.015	0.005	0.045	0.505	114 Lbs/Mft
2016-4SPSN	4	0.015	0.005	0.06	0.58	189 Lbs/Mft
2016-6SPSN	6	0.015	0.005	0.06	0.65	275 Lbs/Mft
2016-8SPSN	8	0.015	0.005	0.06	0.79	346 Lbs/Mft
2016-10SPSN	10	0.015	0.005	0.08	0.91	410 Lbs/Mft
2016-12SPSN	12	0.015	0.005	0.08	0.96	486 Lbs/Mft
2016-16SPSN	16	0.015	0.005	0.08	1.05	543 Lbs/Mft
2016-20SPSN	20	0.015	0.005	0.08	1.19	785 Lbs/Mft
2016-24SPSN	24	0.015	0.005	0.08	1.32	930 Lbs/Mft

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2014-2SPSN	2	0.015	0.005	0.045	0.56	191 Lbs/Mft
2014-4SPSN	4	0.015	0.005	0.06	0.65	306 Lbs/Mft
2014-6SPSN	6	0.015	0.005	0.06	0.73	370 Lbs/Mft
2014-8SPSN	8	0.015	0.005	0.08	0.88	572 Lbs/Mft
2014-10SPSN	10	0.015	0.005	0.08	1.03	719 Lbs/Mft
2014-12SPSN	12	0.015	0.005	0.08	1.065	864 Lbs/Mft
2014-16SPSN	16	0.015	0.005	0.08	1.19	1088 Lbs/Mft
2014-20SPSN	20	0.015	0.005	0.08	1.32	1271 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.