



Made To Order
Cut To Length
Stocking Program Available

Multi-pair VNTC: Overall Shield

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2018-2PSN	2	0.015	0.005	0.045	0.43	83 Lbs/Mft
2018-4PSN	4	0.015	0.005	0.045	0.48	118 Lbs/Mft
2018-6PSN	6	0.015	0.005	0.045	0.585	160 Lbs/Mft
2018-8PSN	8	0.015	0.005	0.06	0.63	190 Lbs/Mft
2018-10PSN	10	0.015	0.005	0.06	0.71	253 Lbs/Mft
2018-12PSN	12	0.015	0.005	0.06	0.75	290 Lbs/Mft
2018-16PSN	16	0.015	0.005	0.06	0.83	363 Lbs/Mft
2018-20PSN	20	0.015	0.005	0.08	0.96	440 Lbs/Mft
2018-24PSN	24	0.015	0.005	0.08	1.01	508 Lbs/Mft
2018-36PSN	36	0.015	0.005	0.08	1.2	738 Lbs/Mft
2018-50PSN	50	0.015	0.005	0.08	1.42	984 Lbs/Mft

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2016-2PSN	2	0.015	0.005	0.045	0.465	95 Lbs/Mft
2016-4PSN	4	0.015	0.005	0.06	0.525	155 Lbs/Mft
2016-6PSN	6	0.015	0.005	0.06	0.64	235 Lbs/Mft
2016-8PSN	8	0.015	0.005	0.06	0.725	266 Lbs/Mft
2016-8PSN	10	0.015	0.005	0.06	0.79	319 Lbs/Mft
2016-12PSN	12	0.015	0.005	0.08	0.87	393 Lbs/Mft
2016-16PSN	16	0.015	0.005	0.08	0.95	500 Lbs/Mft
2016-20PSN	20	0.015	0.005	0.08	0.9	610 Lbs/Mft
2016-24PSN	24	0.015	0.005	0.08	1.1	731 Lbs/Mft
2016-36PSN	36	0.015	0.005	0.08	1.4	1030 Lbs/Mft

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)

Part Number	# Of Pairs	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2014-2PSN	2	0.015	0.005	0.06	0.56	120 Lbs/Mft
2014-4PSN	4	0.015	0.005	0.06	0.6	355 Lbs/Mft
2014-6PSN	6	0.015	0.005	0.06	0.75	360 Lbs/Mft
2014-8PSN	8	0.015	0.005	0.06	0.77	430 Lbs/Mft
2014-10PSN	10	0.015	0.005	0.08	0.94	598 Lbs/Mft
2014-12PSN	12	0.015	0.005	0.08	0.98	660 Lbs/Mft
2014-16PSN	16	0.015	0.005	0.08	1.08	833 Lbs/Mft
2014-20PSN	20	0.015	0.005	0.08	1.19	1025 Lbs/Mft
2014-24PSN	24	0.015	0.005	0.08	1.32	1248 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.