



Made To Order
Cut To Length
Stocking Program Available

Multi-triad Electronic Cable: MultiShield (Foil & Braid) - PVC Insulated & Jacketed

24 AWG (0,23mm²), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8324SFSB	1	0.035	0,88	0.19	4,8
L8024-2TSFSB	2	0.035	0,81	0.28	7,1
L8024-4TSFSB	4	0.035	0,81	0.32	8,1
L8024-8TSFSB	8	0.035	0,81	0.4	10,1
L8024-12TSFSB	12	0.045	1,14	0.5	12,7
L8024-16TSFSB	16	0.045	1,14	0.56	14,2
L8024-20TSFSB	20	0.045	1,14	0.6	15,2
L8024-24TSFSB	24	0.045	1,14	0.68	17,2
L8024-36TSFSB	36	0.05	1,27	0.78	19,8

22 AWG (0,35mm²), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8322SFSB	1	0.035	0,88	0.2	5,0
L8022-2TSFSB	2	0.035	0,88	0.3	7,6
L8022-4TSFSB	4	0.035	0,88	0.35	8,8
L8022-8TSFSB	8	0.035	0,88	0.45	11,4
L8022-12TSFSB	12	0.045	1,14	0.55	13,9
L8022-16TSFSB	16	0.045	1,14	0.61	15,5
L8022-20TSFSB	20	0.045	1,14	0.67	17,0

20 AWG (0,56mm²), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-2TSFSB	2	0.035	0,88	0.39	9,9
L8020-4TSFSB	4	0.035	0,88	0.45	11,4
L8020-8TSFSB	8	0.045	1,14	0.6	15,2
L8020-12TSFSB	12	0.05	1,27	0.74	18,7
L8020-16TSFSB	16	0.05	1,27	0.82	20,8

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

18 AWG (0,81mm ²), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8018-2TSFSB	2	0.035	0,81	0.42	10,6
L8018-4TSFSB	4	0.045	0,81	0.5	12,7
L8018-8TSFSB	8	0.045	0,81	0.66	16,7
L8018-12TSFSB	12	0.05	1,35	0.8	20,3
L8018-16TSFSB	16	0.06	1,35	0.91	23,1

*Tables are illustrative and not exhaustive. Please consult the factory for more information.