



Made To Order  
Cut To Length  
Stocking Program Available

**Multi-triad PLTC: Overall Shield**

20 AWG (0,91mm), 7/.0121 (7x0,32mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Triads	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2TSN20	2	0.05	1,27	0.39	9,90	72
PLTC4TSN20	4	0.05	1,27	0.47	11,93	112
PLTC8TSN20	8	0.05	1,27	0.61	15,49	200
PLTC12TSN20	12	0.06	1,52	0.74	18,76	277
PLTC16TSN20	16	0.06	1,52	0.82	20,82	346
PLTC20TSN20	20	0.06	1,52	0.902	22,91	490
PLTC24TSN20	24	0.07	1,78	1.02	25,9	612
PLTC36TSN20	36	0.07	1,78	1.17	29,71	706

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Triads	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2TSN18	2	0.05	1,07	0.48	12,19	90
PLTC4TSN18	4	0.05	1,27	0.53	13,46	145
PLTC8TSN18	8	0.06	1,52	0.73	18,54	220
PLTC12TSN18	12	0.06	1,52	0.86	21,84	372
PLTC16TSN18	16	0.07	1,78	0.98	24,89	446
PLTC20TSN18	20	0.07	1,78	1.125	28,57	495
PLTC24TSN18	24	0.07	1,78	1.18	29,97	595
PLTC36TSN18	36	0.08	2,03	1.38	35,05	992

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Triads	Jacket Thickness		Nominal OD		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2TSN16	2	0.05	1,27	0.53	9,32	120
PLTC4TSN16	4	0.05	1,27	0.59	12,75	195
PLTC8TSN16	8	0.06	1,52	0.8	19,96	350
PLTC12TSN16	12	0.07	1,78	0.97	24,64	520
PLTC16TSN16	16	0.07	1,78	1.08	27,31	672
PLTC20TSN16	20	0.08	2,03	1.145	29,08	750
PLTC24TSN16	24	0.08	2,03	1.38	33,27	900

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.