



Made To Order
Cut To Length
Stocking Program Available

Multi-triad VNTC: Individual & Overall Shielded

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.020" (0,51mm)

| Part Number | # Of Triads | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight |
|-------------|-------------|----------|------------|-------------|---------|-------------|
| 2018-2STSN | 2 | 0.015 | 0.005 | 0.045 | 0.49 | 120 Lbs/Mft |
| 2018-4STSN | 4 | 0.015 | 0.005 | 0.06 | 0.61 | 210 Lbs/Mft |
| 2018-6STSN | 6 | 0.015 | 0.005 | 0.06 | 0.74 | 280 Lbs/Mft |
| 2018-8STSN | 8 | 0.015 | 0.005 | 0.08 | 0.91 | 350 Lbs/Mft |
| 2018-10STSN | 10 | 0.015 | 0.005 | 0.08 | 1 | 470 Lbs/Mft |
| 2018-12STSN | 12 | 0.015 | 0.005 | 0.08 | 1.1 | 550 Lbs/Mft |
| 2018-16STSN | 16 | 0.015 | 0.005 | 0.08 | 1.24 | 720 Lbs/Mft |
| 2018-20STSN | 20 | 0.015 | 0.005 | 0.08 | 1.3 | 870 Lbs/Mft |
| 2018-24STSN | 24 | 0.015 | 0.005 | 0.08 | 1.43 | 920 Lbs/Mft |

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.020" (0,51mm)

| Part Number | # Of Triads | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight |
|-------------|-------------|----------|------------|-------------|---------|-------------|
| 2016-2STSN | 2 | 0.015 | 0.005 | 0.045 | 0.53 | 160 Lbs/Mft |
| 2016-4STSN | 4 | 0.015 | 0.005 | 0.06 | 0.69 | 230 Lbs/Mft |
| 2016-6STSN | 6 | 0.015 | 0.005 | 0.06 | 0.8 | 340 Lbs/Mft |
| 2016-8STSN | 8 | 0.015 | 0.005 | 0.08 | 0.98 | 490 Lbs/Mft |
| 2016-10STSN | 10 | 0.015 | 0.005 | 0.08 | 1.08 | 525 Lbs/Mft |
| 2016-12STSN | 12 | 0.015 | 0.005 | 0.08 | 1.12 | 590 Lbs/Mft |
| 2016-16STSN | 16 | 0.015 | 0.005 | 0.08 | 1.23 | 695 Lbs/Mft |
| 2016-20STSN | 20 | 0.015 | 0.005 | 0.08 | 1.277 | 850 Lbs/Mft |

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)

| Part Number | # Of Triads | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight |
|-------------|-------------|----------|------------|-------------|---------|--------------|
| 2014-2STSN | 2 | 0.015 | 0.005 | 0.06 | 0.615 | 182 Lbs/Mft |
| 2014-4STSN | 4 | 0.015 | 0.005 | 0.06 | 0.75 | 382 Lbs/Mft |
| 2014-6STSN | 6 | 0.015 | 0.005 | 0.08 | 0.9 | 546 Lbs/Mft |
| 2014-8STSN | 8 | 0.015 | 0.005 | 0.08 | 0.975 | 728 Lbs/Mft |
| 2014-10STSN | 10 | 0.015 | 0.005 | 0.08 | 1.145 | 910 Lbs/Mft |
| 2014-12STSN | 12 | 0.015 | 0.005 | 0.08 | 1.25 | 1092 Lbs/Mft |
| 2014-16STSN | 16 | 0.015 | 0.005 | 0.08 | 1.385 | 1424 Lbs/Mft |
| 2014-20STSN | 20 | 0.015 | 0.005 | 0.08 | 1.434 | 1820 Lbs/Mft |

*Tables are illustrative and not exhaustive. Please consult the factory for more information.