



Made To Order
Cut To Length
Stocking Program Available

Multi Conductor PLTC: Overall Shield

20 AWG (0,91mm), 7/.0121 (7x0,32mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC10C20SF	10	0.04	1,02	0.356	9,04	75.6
PLTC20C20SF	20	0.05	1,27	0.456	11,58	137.5
PLTC30C20SF	30	0.05	1,27	0.54	13,71	193.2
PLTC40C20SF	40	0.05	1,27	0.6	15,24	246.3
PLTC50C20SF	50	0.06	1,52	0.678	17,22	311.7
PLTC60C20SF	60	0.06	1,52	0.736	18,69	365.8
PLTC70C20SF	70	0.06	1,52	0.784	19,91	418.6
PLTC80C20SF	80	0.06	1,52	0.832	21,13	471.4

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2C18SF	2	0.035	0,89	0.209	5,31	29.2
PLTC4C18SF	4	0.035	0,89	0.255	6,48	46
PLTC10C18SF	10	0.04	1,01	0.384	9,75	99.4
PLTC20C18SF	20	0.05	1,27	0.492	12,50	184.1
PLTC30C18SF	30	0.05	1,27	0.585	14,86	262.1
PLTC40C18SF	40	0.06	1,52	0.672	17,07	362.5
PLTC60C18SF	60	0.06	1,52	0.799	20,29	502
PLTC70C18SF	70	0.06	1,52	0.852	21,64	576.9

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.015" (0,38mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C16SF	2	0.035	0,89	0.264	6,70	42.8
PLTC4C16SF	4	0.04	1,01	0.296	7,52	67.6
PLTC15C16SF	15	0.05	1,27	0.517	13,13	206.5
PLTC20C16SF	20	0.05	1,27	0.56	14,22	262.8
PLTC25C16SF	25	0.06	1,52	0.652	16,56	332.8
PLTC30C16SF	30	0.06	1,52	0.688	17,48	388.4
PLTC40C16SF	40	0.06	1,52	0.767	19,48	500.5
PLTC50C16SF	50	0.06	1,52	0.841	21,36	611.9

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C14SF	3	0.04	1,01	0.325	8,23	81.8
PLTC4C14SF	4	0.04	1,01	0.354	8,99	100.8
PLTC10C14SF	10	0.05	1,27	0.552	14,2	225.3
PLTC15C14SF	15	0.06	1,52	0.651	16,5	326.2
PLTC20C14SF	20	0.06	1,52	0.704	17,9	417.6
PLTC30C14SF	30	0.06	1,52	0.842	21,4	600.3
PLTC40C14SF	40	0.07	1,78	0.962	24,4	796.2
PLTC50C14SF	50	0.07	1,78	1.057	26,8	1005.4

12 AWG (2,34mm), 7/.0305 (7x0,77mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C12	3	0.04	1,01	0.368	9,35	113.9
PLTC4C12	4	0.05	1,27	0.422	10,7	148.9
PLTC10C12	10	0.06	1,52	0.552	14,0	353.5
PLTC15C12	15	0.06	1,52	0.744	18,9	466.1
PLTC20C12	20	0.06	1,52	0.807	20,5	598.8
PLTC30C12	30	0.07	1,78	0.99	25,1	884.3
PLTC40C12	40	0.07	1,78	1.108	28,1	1149.2

*Tables are illustrative and not exhaustive. Please consult the factory for more information.