



Made To Order
Cut To Length
Stocking Program Available

MULTI CONDUCTOR PLTC: UNSHIELDED

20 AWG (0,91mm), 7/.0121 (7x0,32mm), Insulation Thickness: 0.015" (0,38mm)

	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC10C20	10	0.04	1,02	0.352	8,94	72.6
PLTC20C20	20	0.05	1,27	0.452	11,48	134.5
PLTC30C20	30	0.05	1,27	0.536	13,61	190.2
PLTC40C20	40	0.05	1,27	0.596	15,14	243.3
PLTC50C20	50	0.06	1,52	0.674	17,12	308.7
PLTC60C20	60	0.06	1,52	0.732	18,59	362.8
PLTC70C20	70	0.06	1,52	0.78	19,81	415.6
PLTC80C20	80	0.06	1,52	0.828	21,03	468.4

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.015" (0,38mm)

	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC2C18	2	0.035	0,89	0.205	5,20	26.2
PLTC4C18	4	0.035	0,89	0.251	6,38	43
PLTC10C18	10	0.04	1,01	0.38	9,65	96.4
PLTC20C18	20	0.05	1,27	0.488	12,40	181.1
PLTC30C18	30	0.05	1,27	0.581	14,76	259.1
PLTC40C18	40	0.06	1,52	0.668	16,97	359.5
PLTC60C18	60	0.06	1,52	0.795	20,19	499
PLTC70C18	70	0.06	1,52	0.848	21,54	573.9

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.015" (0,38mm)

	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C16	3	0.035	0,89	0.26	6,60	36.8
PLTC4C16	4	0.04	1,01	0.292	7,42	61.6
PLTC15C16	15	0.05	1,27	0.513	13,03	200.5
PLTC20C16	20	0.05	1,27	0.556	14,12	256.2
PLTC25C16	25	0.06	1,52	0.648	16,46	326.8
PLTC30C16	30	0.06	1,52	0.684	17,37	382.4
PLTC40C16	40	0.06	1,52	0.763	19,38	494.5
PLTC50C16	50	0.06	1,52	0.837	21,26	605.9

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
Cut To Length
Stocking Program Available

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C14	3	0.04	1,01	0.321	8,15	72.8
PLTC4C14	4	0.04	1,01	0.35	8,89	91.8
PLTC10C14	10	0.05	1,27	0.548	13,9	216.3
PLTC15C14	15	0.06	1,52	0.647	16,4	319.2
PLTC20C14	20	0.06	1,52	0.7	17,8	408.6
PLTC30C14	30	0.06	1,52	0.838	21,3	591.3
PLTC40C14	40	0.07	1,78	0.958	24,3	787.2
PLTC50C14	50	0.07	1,78	1.053	26,7	966.4

12 AWG (2,34mm), 7/.0305 (7x0,77mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter		Weight Lbs/Mft
		Inches	mm	Inches	mm	
PLTC3C12	3	0.04	1,01	0.364	9,25	101.9
PLTC4C12	4	0.05	1,27	0.418	10,6	136.4
PLTC10C12	10	0.06	1,52	0.548	13,9	341.5
PLTC15C12	15	0.06	1,52	0.74	18,8	454.1
PLTC20C12	20	0.06	1,52	0.803	20,4	586.8
PLTC30C12	30	0.07	1,78	0.986	25,0	872.3
PLTC40C12	40	0.07	1,78	1.104	28,0	1137.2

*Tables are illustrative and not exhaustive. Please consult the factory for more information.