



Made To Order
Cut To Length
Stocking Program Available

Multi Conductor VNTC: Overall Shield

18 AWG (1,17mm), 7/.0152 (7x0,39mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2318SF	3	0.015	0.005	0.045	0.29	48 Lbs/Mft
2518SF	5	0.015	0.005	0.045	0.34	69 Lbs/Mft
2918SF	9	0.015	0.005	0.045	0.425	107 Lbs/Mft
2018-12CSF	12	0.015	0.005	0.045	0.465	133 Lbs/Mft
2018-15CSF	15	0.015	0.005	0.045	0.51	160 Lbs/Mft
2018-19CSF	19	0.015	0.005	0.045	0.58	210 Lbs/Mft
2018-25CSF	25	0.015	0.005	0.045	0.655	269 Lbs/Mft
2018-37CSF	37	0.015	0.005	0.045	0.759	374 Lbs/Mft

16 AWG (1,47mm), 7/.0192 (7x0,49mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2316SF	3	0.015	0.005	0.045	0.31	65 Lbs/Mft
2516SF	5	0.015	0.005	0.045	0.365	91 Lbs/Mft
2916SF	9	0.015	0.005	0.045	0.465	143 Lbs/Mft
2016-12CSF	12	0.015	0.005	0.045	0.505	183 Lbs/Mft
2016-15CSF	15	0.015	0.005	0.06	0.585	236 Lbs/Mft
2016-19CSF	19	0.015	0.005	0.06	0.63	284 Lbs/Mft
2016-25CSF	25	0.015	0.005	0.06	0.715	366 Lbs/Mft
2016-37CSF	37	0.015	0.005	0.06	0.87	516 Lbs/Mft

14 AWG (1,83mm), 7/.0242 (7x0,61mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2314SF	3	0.015	0.005	0.045	0.345	90 Lbs/Mft
2514SF	5	0.015	0.005	0.045	0.405	126 Lbs/Mft
2014-9CSF	9	0.015	0.005	0.045	0.51	200 Lbs/Mft
2014-15CSF	15	0.015	0.005	0.06	0.65	330 Lbs/Mft
2014-19CSF	19	0.015	0.005	0.06	0.7	402 Lbs/Mft
2014-25CSF	25	0.015	0.005	0.06	0.795	516 Lbs/Mft
2014-30CSF	30	0.015	0.005	0.08	0.9	644 Lbs/Mft
2014-37CSF	37	0.015	0.005	0.08	0.97	771 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
Cut To Length
Stocking Program Available

12 AWG (2,34mm), 7/.0305 (7x0,77mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2312SF	3	0.015	0.005	0.045	0.39	128 Lbs/Mft
2512SF	5	0.015	0.005	0.045	0.46	179 Lbs/Mft
2912SF	9	0.015	0.005	0.06	0.615	317 Lbs/Mft
2012-15CSF	15	0.015	0.005	0.06	0.74	474 Lbs/Mft
2012-19CSF	19	0.015	0.005	0.06	0.8	578 Lbs/Mft
2012-25CSF	25	0.015	0.005	0.08	0.95	780 Lbs/Mft
2012-30CSF	30	0.015	0.005	0.08	1.029	920 Lbs/Mft
2012-37CSF	37	0.015	0.005	0.08	1.11	1110 Lbs/Mft

10 AWG (2,92mm), 7/.0385 (7x0,98mm), Insulation Thickness: 0.020" (0,51mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2310SF	3	0.02	0.005	0.045	0.454	174 Lbs/Mft
2410SF	4	0.02	0.005	0.045	0.5	218 Lbs/Mft
2510SF	5	0.02	0.005	0.06	0.579	272 Lbs/Mft
2710SF	7	0.02	0.005	0.06	0.63	351 Lbs/Mft
2910SF	9	0.02	0.005	0.06	0.734	451 Lbs/Mft
2010-12CSF	12	0.02	0.005	0.06	0.805	583 Lbs/Mft

8 AWG (3,70mm), 7/.0486 (7x1,23mm), Insulation Thickness: 0.035" (0,89mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2308SF	3	0.03	0.005	0.06	0.589	260 Lbs/Mft
2408SF	4	0.03	0.005	0.06	0.645	332 Lbs/Mft
2508SF	5	0.03	0.005	0.06	0.707	404 Lbs/Mft
2708SF	7	0.03	0.005	0.06	0.772	476 Lbs/Mft
2908SF	9	0.03	0.005	0.08	0.944	720 Lbs/Mft
2008-12CSF	12	0.03	0.005	0.08	1.061	931 Lbs/Mft

6 AWG (4,67mm), 7/.0612 (7x1,55mm), Insulation Thickness: 0.035" (0,89mm)						
Part Number	# Of Conductors	PVC (in)	Nylon (in)	Jacket (in)	OD (in)	Weight
2306SF	3	0.03	0.005	0.06	0.671	373 Lbs/Mft
2406SF	4	0.03	0.005	0.06	0.737	479 Lbs/Mft
2506SF	5	0.03	0.005	0.06	0.81	585 Lbs/Mft
2706SF	7	0.03	0.005	0.08	0.926	822 Lbs/Mft
2906SF	9	0.03	0.005	0.08	1.082	1041 Lbs/Mft
2006-12CSF	12	0.03	0.005	0.08	1.219	1354 Lbs/Mft

*Tables are illustrative and not exhaustive. Please consult the factory for more information.