



Made To Order
Cut To Length
Stocking Program Available

Overall Foil Shielded Multi Conductor Cable, PVC Insulated and Jacketed

24 AWG (0,23mm ²), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)					
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8224SF	2	0.03	0,81	0.16	4,1
L8324SF	3	0.03	0,81	0.17	4,3
L8624SF	6	0.03	0,81	0.2	5,1
L8024-10CSF	10	0.03	0,81	0.25	6,3
L8024-20CSF	20	0.03	0,81	0.3	7,6
L8024-30CSF	30	0.03	0,81	0.36	9,2
L8024-40CSF	40	0.03	0,81	0.4	10,2
L8024-50CSF	50	0.03	0,81	0.44	11,3
L8024-60CSF	60	0.03	0,81	0.47	11,9
L8024-70CSF	70	0.03	0,81	0.51	12,9

22 AWG (0,35mm ²), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)					
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8222SF	2	0.03	0,81	0.18	4,6
L8422SF	4	0.03	0,81	0.2	5,1
L8822SF	8	0.03	0,81	0.25	6,4
L8022-15CSF	15	0.03	0,81	0.31	7,9
L8022-30CSF	30	0.03	0,81	0.4	10,2
L8022-50CSF	50	0.03	0,81	0.49	12,5
L8022-70CSF	70	0.05	1,35	0.62	14,0

20 AWG (0,56mm ²), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-10CSF	10	0.03	0,81	0.35	8,9
L8020-15CSF	15	0.03	0,81	0.41	10,4
L8020-20CSF	20	0.03	0,81	0.46	11,6
L8020-25CSF	25	0.03	0,81	0.5	12,7
L8020-30CSF	30	0.03	0,81	0.54	13,6
L8020-40CSF	40	0.05	1,35	0.65	16,4
L8020-50CSF	50	0.05	1,35	0.71	17,9

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

18 AWG (0,81mm²), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8618SF	6	0.03	0,81	0.31	7,9
L8818SF	8	0.03	0,81	0.33	8,3
L8018-10CSF	10	0.03	0,81	0.39	9,9
L8018-20CSF	20	0.03	0,81	0.51	13,0
L8018-30CSF	30	0.05	1,35	0.64	16,4
L8018-40CSF	40	0.05	1,35	0.72	18,3
L8018-50CSF	50	0.05	1,35	0.79	20,1
L8018-60CSF	60	0.08	2,11	0.91	23,2

16 AWG (1,23mm²), 19/0.0117 (19x0,29mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Conductors	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8316SF	3	0.03	0,81	0.29	5,2
L8416SF	4	0.03	0,81	0.32	6,4
L8016-15CSF	15	0.03	0,81	0.52	7,9
L8016-20CSF	20	0.05	1,35	0.63	10,3
L8016-25CSF	25	0.05	1,35	0.68	13,7
L8016-30CSF	30	0.05	1,35	0.73	18,6
L8016-40CSF	40	0.08	2,11	0.89	22,6
L8016-50CSF	50	0.08	2,11	0.96	24,5

*Tables are illustrative and not exhaustive. Please consult the factory for more information.