



Made To Order
Cut To Length
Stocking Program Available

Unshielded Multi-triad Cable, PVC Insulated and Jacketed

24 AWG (0,23mm²), 7/32 (7x0,20mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8324	1	0.035	0,88	0.17	4,3
L8024-2T	2	0.035	0,81	0.26	6,6
L8024-4T	4	0.035	0,81	0.3	7,6
L8024-8T	8	0.035	0,81	0.38	9,6
L8024-12T	12	0.045	1,14	0.48	12,2
L8024-16T	16	0.045	1,14	0.54	13,7
L8024-20T	20	0.045	1,14	0.58	14,7
L8024-24T	24	0.045	1,14	0.66	16,7
L8024-36T	36	0.05	1,27	0.76	19,3

22 AWG (0,35mm²), 7/30 (7x0,25mm), Insulation Thickness: 0.010" (0,25mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8322	1	0.035	0,88	0.18	4,6
L8022-2T	2	0.035	0,88	0.28	7,1
L8022-4T	4	0.035	0,88	0.33	8,4
L8022-8T	8	0.035	0,88	0.43	10,9
L8022-12T	12	0.045	1,14	0.53	13,4
L8022-16T	16	0.045	1,14	0.59	14,9
L8022-20T	20	0.045	1,14	0.65	16,5

20 AWG (0,56mm²), 7/28 (7x0,32mm), Insulation Thickness: 0.015" (0,43mm)

Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8020-2T	2	0.035	0,88	0.37	9,4
L8020-4T	4	0.035	0,88	0.43	10,9
L8020-8T	8	0.045	1,14	0.58	14,7
L8020-12T	12	0.05	1,27	0.72	18,2
L8020-16T	16	0.05	1,27	0.8	20,3

*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order
 Cut To Length
 Stocking Program Available

18 AWG (0,81mm ²), 16/30 (16x0,25mm), Insulation Thickness: 0.015" (0,43mm)					
Part Number	# Of Triads	Jacket Thickness		Nominal Diameter	
		Inches	mm	Inches	mm
L8018-2T	2	0.035	0,81	0.4	10,1
L8018-4T	4	0.045	0,81	0.48	12,1
L8018-8T	8	0.045	0,81	0.64	16,2
L8018-12T	12	0.05	1,35	0.78	19,8
L8018-16T	16	0.06	1,35	0.89	22,6

*Tables are illustrative and not exhaustive. Please consult the factory for more information.