



Made To Order  
Cut To Length  
Stocking Program Available

Wind Turbine Tray Cable: Unshielded

| 18 AWG (41/34) |                 |          |            |             |         |             |
|----------------|-----------------|----------|------------|-------------|---------|-------------|
| Part Number    | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| WT318          | 3               | 0.015    | 0.005      | 0.045       | 0.285   | 44 Lbs/Mft  |
| WT518          | 5               | 0.015    | 0.005      | 0.045       | 0.335   | 65 Lbs/Mft  |
| WT918          | 9               | 0.015    | 0.005      | 0.045       | 0.42    | 103 Lbs/Mft |
| WT018-12C      | 12              | 0.015    | 0.005      | 0.045       | 0.46    | 129 Lbs/Mft |
| WT018-15C      | 15              | 0.015    | 0.005      | 0.045       | 0.505   | 156 Lbs/Mft |
| WT018-19C      | 19              | 0.015    | 0.005      | 0.045       | 0.575   | 206 Lbs/Mft |
| WT018-25C      | 25              | 0.015    | 0.005      | 0.045       | 0.65    | 265 Lbs/Mft |
| WT018-37C      | 37              | 0.015    | 0.005      | 0.045       | 0.755   | 370 Lbs/Mft |

| 16 AWG (65/34) |                 |          |            |             |         |             |
|----------------|-----------------|----------|------------|-------------|---------|-------------|
| Part Number    | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| WT316          | 3               | 0.015    | 0.005      | 0.045       | 0.305   | 59 Lbs/Mft  |
| WT516          | 5               | 0.015    | 0.005      | 0.045       | 0.36    | 85 Lbs/Mft  |
| WT916          | 9               | 0.015    | 0.005      | 0.045       | 0.46    | 137 Lbs/Mft |
| WT016-12C      | 12              | 0.015    | 0.005      | 0.045       | 0.5     | 177 Lbs/Mft |
| WT016-15C      | 15              | 0.015    | 0.005      | 0.06        | 0.58    | 230 Lbs/Mft |
| WT016-19C      | 19              | 0.015    | 0.005      | 0.06        | 0.625   | 278 Lbs/Mft |
| WT016-25C      | 25              | 0.015    | 0.005      | 0.06        | 0.71    | 360 Lbs/Mft |
| WT016-37C      | 37              | 0.015    | 0.005      | 0.06        | 0.865   | 510 Lbs/Mft |

| 14 AWG (41/30) |                 |          |            |             |         |             |
|----------------|-----------------|----------|------------|-------------|---------|-------------|
| Part Number    | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| WT314          | 3               | 0.015    | 0.005      | 0.045       | 0.34    | 81 Lbs/Mft  |
| WT514          | 5               | 0.015    | 0.005      | 0.045       | 0.4     | 117 Lbs/Mft |
| WT014-9C       | 9               | 0.015    | 0.005      | 0.045       | 0.505   | 191 Lbs/Mft |
| WT014-15C      | 15              | 0.015    | 0.005      | 0.06        | 0.645   | 321 Lbs/Mft |
| WT014-19C      | 19              | 0.015    | 0.005      | 0.06        | 0.695   | 393 Lbs/Mft |
| WT014-25C      | 25              | 0.015    | 0.005      | 0.06        | 0.79    | 507 Lbs/Mft |
| WT014-30C      | 30              | 0.015    | 0.005      | 0.08        | 0.895   | 635 Lbs/Mft |
| WT014-37C      | 37              | 0.015    | 0.005      | 0.08        | 0.965   | 762 Lbs/Mft |

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.



Made To Order  
 Cut To Length  
 Stocking Program Available

| 12 AWG (65x30) |                 |          |            |             |         |              |
|----------------|-----------------|----------|------------|-------------|---------|--------------|
| Part Number    | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight       |
| WT312          | 3               | 0.015    | 0.005      | 0.045       | 0.385   | 114 Lbs/Mft  |
| WT512          | 5               | 0.015    | 0.005      | 0.045       | 0.455   | 165 Lbs/Mft  |
| WT912          | 9               | 0.015    | 0.005      | 0.06        | 0.61    | 293 Lbs/Mft  |
| WT012-15C      | 15              | 0.015    | 0.005      | 0.06        | 0.735   | 460 Lbs/Mft  |
| WT012-19C      | 19              | 0.015    | 0.005      | 0.06        | 0.795   | 564 Lbs/Mft  |
| WT012-25C      | 25              | 0.015    | 0.005      | 0.08        | 0.945   | 769 Lbs/Mft  |
| WT012-30C      | 30              | 0.015    | 0.005      | 0.08        | 1.025   | 908 Lbs/Mft  |
| WT012-37C      | 37              | 0.015    | 0.005      | 0.08        | 1.105   | 1099 Lbs/Mft |

| 10 AWG (105/30) |                 |          |            |             |         |             |
|-----------------|-----------------|----------|------------|-------------|---------|-------------|
| Part Number     | # Of Conductors | PVC (in) | Nylon (in) | Jacket (in) | OD (in) | Weight      |
| WT310           | 3               | 0.02     | 0.005      | 0.045       | 0.45    | 165 Lbs/Mft |
| WT410           | 4               | 0.02     | 0.005      | 0.045       | 0.495   | 209 Lbs/Mft |
| WT510           | 5               | 0.02     | 0.005      | 0.06        | 0.575   | 264 Lbs/Mft |
| WT710           | 7               | 0.02     | 0.005      | 0.06        | 0.625   | 343 Lbs/Mft |
| WT910           | 9               | 0.02     | 0.005      | 0.06        | 0.73    | 443 Lbs/Mft |
| WT010-12C       | 12              | 0.02     | 0.005      | 0.06        | 0.8     | 575 Lbs/Mft |

\*Tables are illustrative and not exhaustive. Please consult the factory for more information.